Cover Styl

E-FILM

GLASS



RANGE & FINISH

FAMILY **Data Privacy**

SUB-FAMILY **Switch**

CHARACTERISTICS

Width (cm)	**100 cm**
Length (m)	**1 m**
Thickness (µm)	**540 µm**
Composition	**PET**
Composition Release liner	**PET**
Storage in recommended conditions	**3 years**
Storage Temperature	**5°C-30°C**
Visible Light Transmission	**91%**
Warranty	**2 years**

CERTIFICATIONS

FIRE RATING (EN13501-1)
M1 (NF P92-507)

REACH / ROHS
Compliant

Non-contractual visuals and data, Cover Styl reserves the right to change the composition of its films at any time. The rendition of the colours and finishes on the computer may vary according to the screen and not give a true representation of the true appearance. We therefore recommend you order a sample on line or contact us so that we can examine the finish that best adapts to your requirements. Due to the slight differences in colour in production runs, we advise you to purchase the amount you require in one go to avoid any difference in appearance in the execution of your Cover Styl project.

Certified B Corporation

Cover Styl

E-FILM

GLASS

APPLICATION, INSTALLATION & MAINTAINANCE

APPLICATION COMPATIBILITY

Facing UV rays	**Caution**

INSTALLATION

Installation Type	**Interior**
Installation Method	**Dry**
Installation Temperature	**12°C-38°C**

INSTALLATION GUIDELINES

- Always clean the glass thoroughly before installation, using Crystal Antistatic Spray (600-ATS) and wear antistatic gloves during installation or handling.
- Apply dry only - never use water or soapy solution.
- Handle carefully: keep the film flat, do not bend, and protect the edges.
- Keep the top protective liner in place until the end of the installation.
- Do not install under frames or in areas subject to mechanical stress.
- Leave a 2-2.5 mm gap if installing multiple panels side by side.
- Sealing is not mandatory but recommended if the film is exposed to humidity or at risk of water contact. Use only neutral (non-acidic) silicone sealant along the film edge.
- All electrical connections must be performed by a licensed electrician, following the wiring diagram and using the recommended transformer.
- For best durability, avoid continuous ON mode - use a timer to ensure a daily power cutoff.

Wait 30 days before cleaning and only use a microfiber cloth with non-abrasive products.

MAINTENANCE GUIDELINES

Wait 30 days after installation before cleaning the E-Film surface.

Use a soft, lint-free microfiber cloth and a mild cleaning product, such as a 50/50 diluted isopropyl alcohol solution or an ammonia-free glass cleaner.

Wipe gently in one direction to avoid streaks.

Clean power switches and controllers with a dry cloth only.

Non-contractual visuals and data, Cover Styl reserves the right to change the composition of its films at any time. The rendition of the colours and finishes on the computer may vary according to the screen and not give a true representation of the true appearance. We therefore recommend you order a sample on line or contact us so that we can examine the finish that best adapts to your requirements. Due to the slight differences in colour in production runs, we advise you to purchase the amount you require in one go to avoid any difference in appearance in the execution of your Cover Styl project.

Certified B Corporation