



The window film Spectra 615 C is composed of ceramic to control UV transmissions and solar heat while being completely transparent. With a total thickness of 180 μ , the window film Spectra 615 C can be used as a solution against carjacking.

Certifications



Warranty SOLAR SCREEN®
15 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating
M1



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
152cm

Construction

1. High optical quality polyester with anti IR "nano ceramic" particle deposit
2. Bonding adhesive
3. 100 μ high optical quality polyester
4. Reinforced PS Adhesive to accompany the elasticity of the film in case of impact, glass polymerization within 30 days
5. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	<1%
Visible Light Transmission	85%
Reflection Of External Visible Light	7%
Reflection Of Internal Visible Light	7%
Total Solar Energy Rejected	32%
Total Solar Energy Rejected 2*	28%
Solar Ratio :	
Solar Energy Reflection	9%
Solar Energy Absorption	58%
Solar Energy Transmission	33%
Reduction In Solar Glare	13%
G-Value	0.69
U-Value	5.08
Rejected Infrared (760-2500 Nm)	68%
Shading Coefficient	0.6
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	180 μ
Colour From The Outside	HIGHLY NEUTRAL

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	!
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	!
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✗
Stadip Ext. Clear Double Pane	!
Stadip Int. Clear Double Pane	✗

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.